

House Lighting- LED Spatial Pendants

The Springtree LED Spatial Pendant is an 80°, 120-Watt COB LED House Lighting Fixture.

Options

- RGBWW LED COB Engine
- Warm White LED COB Engine

Key Features

- Vibrant Color Creation – Mix rich colors with RGBWW control
- Powerfully Bright Warm White – Beautiful, even illumination for everyday use
- Full DMX Control – Smooth, professional dimming and scene control
- Clean Open-Barrel Design – Discreetly hides cable ends for a polished installation
- Efficient Triple-Fan Cooling – Designed for long life with low noise output
- Wireless DMX Ready – Built-in 5V connector powers optional Springtree Wireless DMX
- ETL Certified



RGBWW Optical

- Light Source: 120Watt RGBWW COB LED
- Color Temperature: 6000K when all LEDs are at 100%
- Lumens: 3973
- Beam Angle: 80°

Warm White Optical

- Light Source: 120Watt WW COB LED
- Color Temperature: 3200K
- Lumens: 9010
- Beam Angle: 80°

Power

- Requires 14/3 SO Cable (not included) with locking power connectors (included).
- 8 fixtures can be daisy-chained together.
- Up to 13 fixtures can be on one 20amp circuit.

Dimension and Weight

- Dimensions: 8.25" x 20"
- Weight: 8.6 lbs

Operating Mode

- RGBWW: 7 Channel
- Warm White: 2 Channel

Connections

- 3 screw phoenix terminal for DMX In/Out
- 3-pin DMX (3-pin DMX is only for DMX In)
- Linking Power In/Out
- DC5V for Springtree Wireless DMX

Included

- 1x Blue Locking Power Connector
- 1x White Locking Power Connector
- Phoenix Connector

Certifications

- ETL



[Scan for product page]

Dimensions



DMX Traits

RGBWW

CH1	Red	Red Intensity	0~255
CH2	Green	Green Intensity	0~255
CH3	Blue	Blue Intensity	0~255
CH4	Warm White	White Intensity	0~255
CH5	Master Dimmer	Dimmer	0~255
CH6	Strobe	Slow to Fast	0~255
CH7	Macro	See Chart Below	0~255

DMX Traits - Continued

RGBWW Macro Functions

0-10	Nothing
10-129	Cycle through colors, increasing speed
130-249	Cycle through colors with fade in / fade out, increasing speed
250-255	Nothing

Warm White

CH1	Dimmer	0~255
CH2	Strobe Slow to Fast	0~255