

Lo-Vo - LED Spatial Minis

Spatial Minis are mini 25-degree LED spotlights that fit in the palm of your hand.

Optional Accessories

- SpatialMini-U (U-Bracket)
- SpatialMini-Ring (Recessed Ceiling Ring)
- SpatialMini-Cylinder (8cm Frosted Acrylic Cylinder)



SKU: SMini-RGBWW
SMini-WW

Available Options

- RGBWW LEDs
- Warm White LEDs

Warm White Optical

- Powered By 6x 1.5Watt LEDs
- 580 Lumens
- 25° beam angle

RGBWW Optical

- 6x 2Watt LEDs
- 590 Lumens
- 25° beam angle

Power

- 24V Constant Voltage

Dimensions and Weight

- 1 7/8" x 4 1/2"
- .70 lbs

Required Cable


- 18/2 Cable for WW and 18/5 for RGBWW (18 is the gauge, and two or five is how many wires are in the jacket)

*We use 18/6 wire for RGBWW (one extra wire) because it is affordable and in a pull box.



{Scan for product page}


Optional Accessories



RECESSED RING



U-BRACKET



FROSTED ACRYLIC CYLINDER

Spatial Minis can be hung from the ceiling for down-lighting, mounted to a beam or wall using a U-bracket to spotlight at multiple angles or flush-mounted with the Spatial Mini Ring. The Spatial Mini Ring is a recessed ring that allows you to mount the fixture flush with the ceiling, with room for the light to be angled in the ceiling.

Another accessory available for the Spatial Mini is the Spatial Mini Cylinder. It's an 8cm frosted acrylic cylinder that screws onto the end of the Spatial Mini.



{Acrylic Cylinder Lit Red}

Power Drivers (Required)

Power Drivers are the required power and control center of the Lo-Vo lighting fixtures.

Power Driver	DMX150	DMX602XE	DMX1202XE	DMX1802XE
Amount of RGBWW Spatial Minis Powered	12	48	96	120
Amount of Warm White Spatial Minis Powered	15	64	128	156



{Scan to learn more about
Power Drivers}