

## Lo-Vo - LED Spatial Minis

Spatial Minis are mini 25-degree LED spotlights that fit in the palm of your hand.

### Optional Accessories

- SpatialMini-U (U-Bracket)
- SpatialMini-Ring (Recessed Ceiling Ring)
- SpatialMini-Cylinder (8cm Frosted Acrylic Cylinder)



SKU: SpatialMini-RGBWW  
SpatialMini-WW

### Available Options

- RGBWW LEDs
- Warm White LEDs

### Warm White Optical

- Powered By 6x 1.5Watt LEDs
- 580 Lumens
- 25° beam angle

### RGBWW Optical

- 6x 2Watt LEDs
- 590 Lumens
- 25° beam angle

### Power

- 24V Constant Voltage

### Dimensions and Weight

- 1 7/8" x 4 1/2"
- .70 lbs

### Required Cable


- 18/2 Cable for WW and 18/5 for RGBWW (18 is the gauge, and two or five is how many wires are in the jacket)

\*We use 18/6 wire for RGBWW (one extra wire) because it is affordable and in a pull box.



{Scan for product page}


## Optional Accessories



RECESSED RING



U-BRACKET



FROSTED ACRYLIC CYLINDER

Spatial Minis can be hung from the ceiling for down-lighting, mounted to a beam or wall using a U-bracket to spotlight at multiple angles or flush-mounted with the Spatial Mini Ring. The Spatial Mini Ring is a recessed ring that allows you to mount the fixture flush with the ceiling, with room for the light to be angled in the ceiling.

Another accessory available for the Spatial Mini is the Spatial Mini Cylinder. It's an 8cm frosted acrylic cylinder that screws onto the end of the Spatial Mini.



{Acrylic Cylinder Lit Red}

## Power Drivers (Required)

Power Drivers are the required power and control center of the Lo-Vo lighting fixtures.

Power Driver	DMX150	DMX600	DMX1200	DMX1800
Amount of RGBWW Spatial Minis Powered	12	48	96	144
Amount of Warm White Spatial Minis Powered	15	64	128	192



{Scan to learn more about  
Power Drivers}