



F96VW [-WH]

VARIABLE WHITE FRESNEL

EVENT
LIGHTING



Photometrics

Light Source	48W Cool White 5,700K 48W Warm White 2,700K COB LED
Beam Angle	20°~50°
Field Angle:	50°~67°
Output	1,230 lux @ 3m @ 20°, 395 lux @ 3m @ 50°
Lens:	80mm Fresnel
PWM:	1,200Hz
LED Lifespan	50,000 hours

Effects

Dimming	0~100%, 16-bit
Strobe:	1~25Hz
Zoom:	Manual, 20°~50°

Power

Input Voltage	100~240 V AC, 50/60 Hz, 75 W
Connection	True1 in/out

Control

Operation Modes	Manual, Master / Slave & DMX, WDMX (optional)
Control Protocol	DMX512
DMX Channels	1 / 2 / 7
Control Interface	5-pin XLR in/out
Display	LCD control panel with four buttons

Housing

Housing Materials	Die- cast Aluminum Housing
Housing Finishing:	Matte Black or White
Cooling	Fanless Cooling with Temperature Protection
Net Weight	2.3 kg
Barn Door	Included
Gel Clip	Included



Lux @ 20°

F96VW

	1.0m	2.0m	3.0m	4.0m	5.0m
	Ø0.35	Ø0.71	Ø1.06	Ø1.41	Ø1.76
2700K	5,100	1,200	546	298	198
5700K	6,850	1,680	745	422	445
FULL	11,600	2,780	1,230	685	445

Lux @ 50°

	Ø0.93	Ø1.87	Ø2.8	Ø3.73	Ø4.66
	1,550	393	172	106	75
2700K	2,150	530	245	148	104
5700K	3,600	895	395	245	175

Road Case (Optional)

F96VWCASE6

Road Case to suit 6 units
F96VW Fresnels

